



The RPA01 Roving PA Radio Microphone Transmitter is a multi-channel UHF handheld microphone, which is designed to work with the Radio Microphone Receiver installed within the ASL Station Announcement Points, either SAP01 or SAP02. It is normally used for making remote announcements to station platforms.

The unit incorporates an internal aerial and microphone, and has ten selectable channels. The unit features a LCD display to show the selected channel number and the battery level. This Radio Microphone has excellent microphone acoustics, and its front facing microphone gives low susceptibility to acoustic feedback. It also generates a non-standard pilot tone frequency that gates the ASL RMR01/RMR02 Radio Microphone Receivers, to prevent announcements from non-authorized transmitters from being heard.

This lightweight and strong Radio Microphone has large PTT and channel selection buttons, and a symmetrical design, which provides the operator with ergonomic comfort, and easy operation, even while wearing gloves. Strength is ensured by a robust plastic enclosure, and a protective rubber edge strip, which also provides the unit with impact resistance and good water ingress protection.

The unit uses a built-in Lithium Polymer rechargeable battery. This is an advanced battery technology which provides low weight and long run times. A fully charged battery generally lasts for up to 7 hours of continuous talk time, which translates to several days of normal operational use. The RCS01 4-bay RPA Transmitter Charging Station is available, and can be ordered separately if required.

The Radio Microphone Transmitter is supplied with belt clip with lanyard fixing as standard. The standard lanyard is suitable for rail and general transport use, having break-away links to ensure that the user is not injured if the microphone is trapped in moving equipment. The belt clip can be removed by replacing the standard rear plate with a rear plate without belt clip, which is also supplied with the RPA01.

For further details, and for information on other products, please visit www.asl-control.co.uk.

SPECIFICATION

General

Effective Radiating Power (EIRP).....	10 mW
Audio Frequency Response.....	200 Hz – 10 kHz
Antenna.....	internal dipole
Grid Spacing.....	25 kHz
Operating Frequencies	
Channel 1.....	863.050 MHz
Channel 2.....	864.825 MHz
Channel 3.....	863.225 MHz
Channel 4.....	864.675 MHz
Channel 5.....	863.375 MHz
Channel 6.....	864.525 MHz
Channel 7.....	863.525 MHz
Channel 8.....	864.375 MHz
Channel 9.....	863.625 MHz
Channel 10.....	864.225 MHz
Pilot Tone Frequency.....	non-standard compatible with ASL RMR01/RMR02 Radio Microphone Receivers
Battery	
Type.....	VARTA EasyPack 550
Talk Time.....	up to 7 hours
Type.....	Lithium polymer, built-in
Life Time.....	up to 3 years
Life Cycle.....	>1000
Self-discharge... 5% per month (less after first month)	
Format.....	plastic case and buttons
Colour.....	grey case black buttons and rubber strip ¹
Lanyard.....	with breakaway links 8 mm width x 240 mm length ribbon (approx.)

Environmental

Temperature (storage and operating)	-5 °C to +50 °C
Humidity Range	0% to 93% non-condensing

Dimensions and Weight

Dimensions (H x W x D).....	141 mm x 65 mm x 39 mm (including belt clip)
Weight.....	166 g

¹ Refer to ASL for different colour options.



This equipment is designed and manufactured to conform to the following EC standards:

Radio Type Approval: EN 300 422-1:v1.2.2, EN 300 422-2:v1.1.1

EMC: EN 301 489-9:v1.3.1, EN 301 489-1:v 1.6.1, EN 50121-4:2006, ENV 50204:1996

Safety: EN 60065:2002

This product is RoHS compliant.

Manufacturer

Application Solutions (Safety and Security) Ltd.

Unit 17 - Cliffe Industrial Estate - Lewes - East Sussex - BN8 6JL - U.K.

Tel: +44(0)1273 405411 Fax: +44(0)1273 405415

www.asl-control.co.uk



QUALITY ASSURED FIRM
CERTIFICATE NUMBER: 96-LUN-A24-01



All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Application Solutions (Safety and Security) Ltd. assumes no liability with respect to the accuracy of such information.